



## COUNTRY COLOUR

Colourful diversity and unrivalled durability – for all weather conditions!



### DESCRIPTION

An Opaque, satin-matt wood finish for exterior use of unsurpassed durability. Deep rich colours will hide grain and colour of the wood but will allow texture to show through, maintaining the character of the wood.

Country Colour is based on natural oils and microporous, allowing the wood to breathe. It will not crack, flake, peel or blister. It is extremely weather- and UV-resistant, water-repellent and moisture regulating. It has been well-tried for decades under the severest weather conditions (seaside and mountains).

It is viscous, easy to apply and easy to maintain. It has a very high solids content (over 50 %) resulting in extremely large coverage and long durability. Complete coverage in two coats.

Country Colour does not contain biocides nor preservatives and can therefore also be used indoors. It is safe for human, animal and plant when dry and complies with German DIN 53 160 (fast to perspiration and saliva) and EURO Norm EN 71 (suitable for children's toys).

### RECOMMENDED USE

Osmo Country Colour is especially recommended for all woods in the outdoor area where exceptional durability is asked for: Wooden claddings, balconies, win-

dows and window shutters, gates, pergolas, wooden panels, garden furniture and summer houses, carports, etc. Ideal to renew previously stained, weathered wood surfaces or old micro-porous coatings.

### INGREDIENTS

Based on natural vegetable oils (sunflower oil, soybean oil and thistle oil), paraffines, iron oxide- and other organic pigments, titanium dioxide (white pigment), siccatives (drying agents) and other water-repellent additives. Disaromatised white spirit (benzene-free).

This product fulfils EU-Regulation (2004/42/EC) according to the VOC-content of max. 400 g/l (Cat. A/e (2010)).

Detailed declaration of ingredients available upon request.

### TECHNICAL DATA

Specific gravity: 1.0-1.2 g/cm<sup>3</sup>

Viscosity: >70s DIN EN ISO 2431/3 mm, viscid

Odour: Faint/mild, odourless after drying

Flashpoint: 60 °C according to DIN EN ISO 2719



## STORAGE

Shelf life is 5 years or more if can is tightly closed. Store in a dry place. If thickened by frost it will regain a normal consistency under normal temperatures within 24-36 hours.

## SURFACE PREPARATION

Wood surface must be clean, dry and frost-free (moisture content max. 20 %).

Osmo Country Colour is ready to use, please do not thin. Stir well before use.

Old micro-porous stains must be cleaned thoroughly. Old paints and lacquers must be removed. For grinding works generally wear a dust mask.

If possible, please apply the first coat to all sides before installation.

The finished surface is, amongst other things, influenced by the woods' natural characteristics. Basically, a trial application – especially for unfamiliar under-grounds – is required.

If additional protection against blue stain, rot and mildew is desired, pre-treat the wood – if possible all sides – with Osmo WR Base Coat\*.

Leave to dry 12-24 hours before further treatment.

\*Use biocides safely. Always read labelling and product information before application.

## METHOD OF APPLICATION

Apply thinly along the grain using the Osmo Natural Bristle Brush or Osmo Microfibre Roll and spread well. Allow for good ventilation whilst drying. Then apply a second coat – also thinly.

In case of renovation generally 1 coat is enough.

## CLEANING OF TOOLS

With Osmo Brush Cleaner (free from aromatic compounds).

## DRYING TIME

Approx. 10 - 12 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time.

## COVERAGE

1 l covers approximately 26 m<sup>2</sup> with 1 coat.

The coverage of the product depends significantly on the character of the timber. All information refers to smooth and planed/cut surfaces. Other surfaces may lead to another coverage.

## NOTE

In case the surface in the outdoor area shall be given an additional protection (e.g. windows, claddings), over coat with 1 x Osmo UV Protection Oil Clear (410 biocidefree or 420 with film protection) after drying. This helps to protect the wood against dirt and extends the durability of the coating. If you have chosen Country Colour White 2101, please use the Natural Oil Woodstain 900 instead.

The over decades well-tried Country Colour is also available in your required colour. Starting from 1 x 2.5 l you can order this product in 186 RAL Classic and 1950 NCS colour shades, also featured with biocidal film protection upon request.

Some wood species “bleed” natural water soluble ingredients during weathering.

## CAUTION

Keep out of the reach of children. Avoid contact with eyes and skin. In case of contact with eyes, rinse immediately with plenty of water and turn to a doctor. Contains 2-butanonoxime. May produce allergic reaction. In case of swallowing seek medical advice immediately and show the container or label. Use only in well ventilated areas. Caution: Wash out any cloth impregnated with this product immediately or store in an airtight container (danger of self-ignition). The dry finish fulfils classification B2 according to DIN 4102.

Safety data sheet upon request for professional users.

## DISPOSAL

Dispose of product residuals and completely emptied packages according to the local official guidelines (EU-waste code key number 08 01 11). Only fully emptied tins can be recycled.

## COLOUR TONE

- 2101 White
- 2203 Light Ochre
- 2204 Ivory
- 2205 Sunflower Yellow
- 2308 Nordic Red
- 2310 Cedar/ Redwood
- 2311 Signal Red
- 2404 Fir Green
- 2501 Labrador Blue
- 2506 Royal Blue
- 2507 Dove Blue
- 2606 Medium Brown
- 2607 Dark Brown
- 2703 Charcoal
- 2704 Dusk Grey



2708 Pebble Grey  
2716 Anthracite Grey  
2735 Light Grey  
2742 Traffic Grey

CAN SIZES

0.75 l; 2.50 l; 25 l

The above mentioned information is given to the best of our knowledge but without liability.

Dated: 01/14